



CHAMELEON SURFACE ROUND ADJUSTABLE

Surface Mounted



Key Features:

- Up to 1825lm delivered output
- Gear driven tilt 0° to 30° and 360° lockable rotation
- Various beams available upon request of vertical plane
- 5 years limited warranty
- Chicago plenum rated



Technical Data:

Body Material	Die-cast	Delivered Lumen Range	900 lm to 1825 lm
Safety	Chicago Plenum	Output Type	Constant Current
Warranty	5 Years	Driver	Integral
Light Source	COB	Code Compliance	CCEA / CCC / CSA / CE / ETL / JA8
Lifetime	L80/B10 @ 70,000 hours	CRI	90+
Power Range	10W to 22W	CCT	2700K / 3000K / 3500K / 4000K / Tunable White / Dim to Warm / RGBW

Housing Code :

Code Example: SCHS210N

SCHS	Power	Voltage	Control	Housing	Emergency
Type					
SCHS	Mono:	2	0	O	N
	L	240-220V	Non-Dim	Octagonal J-Box	No
	10 W - 960 lm	U	1	N	9
		Universal 120 to 277V	0-10 to 1%	No J-Box	90 mins
	M		2		
	12 W - 1150 lm		0-10 Fade-off		
	H		D		
	18 W - 1740 lm		DALI		
	V		P		
	22 W - 2130 lm		Phase ELV & Triac		
	Dim to Warm:		L		
	L		Lutron		
	10 W - 890 lm		X		
			DMX		
	M				
	18 W - 1720 lm				
	Tunable White:				
	L				
	10 W - 640 lm				
	M				
	18 W - 870 lm				
	RGBW:				
	L				
	4 W - 340 lm				

Module Code :

Code Example: SCMSALWWDS9270

▼ Fill in the same **power** code value for the housing and module.

SCMSA	Power	Body Finish	Baffles Finish	UL Rating	Optics Type	CRI	CCT	Accessory
Type								
SCMSA	Mono:	W	W	D	S	9	27	O
	L	White	Flat White	Dry	10°	90+	2700K	None
	10 W - 960 lm	B	B	W	M	H	30	T
		Black	Flat Black	Wet	25°	Thrive	3000K	Clear Lens
	M	G	N		F		35	L
	12 W - 1150 lm	Grey	Black Nickel		35°		3500K	Diffuse Lens
	H	S	C		W		40	F
	18 W - 1740 lm	Silver	Specular Chrome		50°		4000K	Elliptical Lens
	X	Custom	D				WD	
			Diffuse Chrome				3000K - 1800K	
	V		G				TW	
	22 W - 2130 lm		Bright Gold				2700K - 6500K	
	Dim to Warm:		E				CC	
	L		Diffuse Gold				RGBW	
	10 W - 890 lm		X					
			Custom					
	M							
	18 W - 1720 lm							
	Tunable White:							
	L							
	10 W - 640 lm							
	M							
	18 W - 870 lm							
	RGBW:							
	L							
	4 W - 340 lm							



Notes:


1. Denotes output at 3000K, unless otherwise noted.
2. Denotes output specific to Dim-to-Warm at 3000K.
3. Denotes output specific to Tunable White.
4. Denotes output specific to RGBW.
5. Not applicable for ELV dimming.
6. Hi-lume, Vive, and Athena compatible.
7. Only available with DMX dimming.
8. Not applicable for integral driver.



Optical Flexibility:


CHAMELEON ROUND ADJUSTABLE NARROW DISTRIBUTION 10°

Narrow Distribution 10°




CHAMELEON ROUND ADJUSTABLE MEDIUM DISTRIBUTION 25°

Medium Distribution 25°




CHAMELEON ROUND ADJUSTABLE FLOOD DISTRIBUTION 35°

Flood Distribution 35°



CHAMELEON ROUND ADJUSTABLE WIDE DISTRIBUTION 50°


Wide Distribution 50°




BEAM DISTRIBUTION AND COMBINATION



15°x60°
10°+ Elliptical
spread lens
(10x60)



25°x60°
25°+ Elliptical
spread lens
(10x60)



40°x60°
35°+ Elliptical
spread lens
(10x60)



10°+ Diffuse lens



25°+ Diffuse lens





50°+ Diffuse lens

Delivered Lumen Output:

Output		Watts		CRI +90			
STATIC-WHITE				2700K	3000K	4000K	
L	10W	900 lm		960 lm		1250 lm	
M	12W	1080 lm		1150 lm		2250 lm	
H	18W	1630 lm		1740 lm		2250 lm	
V	22W	1990 lm		2130 lm		2250 lm	
DIM-TO-WARM 3000K-3000K				3000K			
L	10W			890 lm			
M	18W			1720 lm			
TUNABLE WHITE 2700K-6500K				2700K	6500K		
L	10W	640 lm				750 lm	
M	18W	870 lm				1050 lm	
RGBW		R		G		B	W
Total	4W	60 lm		340 lm		60 lm 260 lm	

Mounting Flexibility:

SURFACE MOUNTED



Housing:

Octagonal J-box

